



## **Rhino Top Installation Instructions**

**1-001**

Remove top from packaging.

Hardware consists of:

- 8ea. 1/4-20 X 3/4 BHCS SS
- 8ea. 1/4-20 NYLOCK NUTS
- 4ea. #28 LOOP STRAP
- 4ea. #24 LOOP STRAP

1. Place roof onto roll cage with the long side toward the back. Rear rain gutter should be approx. 7-1/4in. from top of seat belt bracket for proper placement.
2. Insert the small clamps (SS-24E) onto the two cross bars, aligning the holes in the roof with the holes in clamps.
3. Insert bolts through the roof from top.
4. Apply lock nut to bolt and leave loose until all fasteners are installed and roof is in final position.
5. Repeat steps 2-4 for outer clamps.
6. Adjust roof, centering top to best fit watching for equal coverage on side bars while insuring that the front edge of roof is parallel to the ground.
7. Starting with the 2 inner bolts at rear tighten completely
8. Tighten 2 inner bolts at front cross bar.
9. Repeat steps 7, 8 for outer bolts.
10. Enjoy!!!!

If you have any questions, please call 423-569-3478 or visit [www.dirtperformance.net](http://www.dirtperformance.net) ,  
e-mail question to [producttech@dirtperformance.net](mailto:producttech@dirtperformance.net).